

**Reflex Exdirt D 3/4, threaded dirt  
separator, 110 °C, 10 bar  
Article-No.:9252010**



Reflex Exdirt,  
dirt and sludge separator for heating  
and cooling systems respectively for  
sealed system circuits.

Suitable for use with water and  
water/glycol mixture to a maximum of 50%  
concentration.

Fitting for the removal of dirt par-  
ticles up to a size of 5,0 µm out of  
the liquid flow by way of a specifi-  
cally designated insert.

The collection area can be easily  
emptied at regular intervals using a  
drain ball valve while the system re-  
mains in operation. The flanged collec-  
tion chamber can be removed for inspec-  
tion.

---

## **Merkmale**

Type: D 3/4  
Housing material: Messing  
Installation model: horizontal  
Connection type: Gewinde  
System connection: G 3/4  
Drain connection: G 3/4  
max. operating pressure: 10 bar  
max. operating temperature: 110 °C  
max. flow: 1,25 m<sup>3</sup>/h  
kvs: 10,7 m<sup>3</sup>/h  
Length: 85 mm  
Height: 116 mm  
Diameter: 65 mm  
Weight: 1 kg



25.05.2018 16:34

### **Reflex Winkelmann GmbH**

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • [www.reflex.de](http://www.reflex.de)  
Geschäftsführer: Norbert Hülsmann, Volker Mauel  
USt.-Ident.-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen